

DENTIX[®] X-Stream

DENTAL RADIOGRAPHIC FILM



Characteristic

DENTIX X-Stream is a double-emulsion extra high speed non-screen X-ray film (ISO Class E-F) with high contrast and low fine grain. The film has high image quality and outstanding detail definition. The film is intended for direct-exposure routine intraoral radiographs.

This extra high speed of the film enables to reduce the X-ray dose of 50 % in comparison with the dental films of D class and of 20% in comparison with E class.

Film base

DENTIX X-Stream is coated on a dimensionally-stable bluish 0.175 mm thick polyester film base. The film is provided, on both sides, with protective and antistatic layers preserving the film against mechanical damages and eliminating the static charge.

Packing

Each sheet of film is enclosed in a light-tight plastic envelope.

size ISO	size [mm]	number of films in one packet	number of packets in one packing
0	22.0x35.0	1	100
2	30.5x40.5	1	150
2	30.5x40.5	2	150

This soft and hygienic packing protects the patient, facilitates manipulation with the film and enables disinfecting the cover with common disinfectants.

Every film packet is protected with a lead sheet on the side opposite to radiation source (marked as back-side on the packet). Each film is provided with an embossed dot located near the edge of the film that serves as an identifier of the radiation side on the processed film. Its raised portion indicates the side facing the radiation source.

Darkroom illumination

DENTIX X-Stream can be exposed in daylight. The processing shall be carried out in a darkroom using indirect dark-red or olive-green safelight. Recommended safelight filters are: KODAK GBX-2, Agfa R1 (dark-red), Agfa G7 (olive-green).

Processing

DENTIX X-STREAM can be processed manually or in processors. The FOMADENT concentrated solutions are recommended for processing the film to obtain the best results, but any good trademarked chemicals may be used too. The film is possible to be processed in all common types of processors. Results depend on duration of processing cycle and adjusted temperature.

automatic processing	manual processing – developing
4.5–5.0 min / 25 °C	5.0 min / 20°C 4.0 min / 22°C 3.5 min / 24 °C 1.5 min / 28 °C

Exposure conditions for DENTIX X-Stream

X-ray apparatus adjustment: 50 – 70 kV and 7 – 15 mA

(use correct values recommended by the apparatus manufacturer)

Adjustment: 65 kV, 8 mA, 20 cm focus-film distance			
Maxillary	Exposure	Mandibular	Exposure
Frontal	0.13 s	Frontal	0.10 s
Premolar	0.17 s	Premolar	0.11s
Molar	0.19 s	Molar	0.13 s

For making exposures of children reduce the exposure time approx. by 33%.
For making exposures of empty patches reduce the exposure time approx. by 25 %.
For obtaining the possibly best results all the necessary changes of exposure parameters (i.e. exposure time, mA, kV or any changes of the focus-film distance) shall be reflected in other parameters.

Storage

DENTIX X-Stream should be stored in the original packing in a dry and cool place at a temperature from 10 °C to 21 °C and a relative humidity of 40 – 60% protected from damaging fumes, gases and ionizing radiation. For long-term storage the film should be stored in a refrigerator. Before use, the film in the intact original packaging should be allowed to adjust to room conditions for at least 2 – 4 hours.

Warning

The usage and processing of the DENTIX X-Stream film result to wastes that are classified as dangerous gifts and for this reason an ecological liquidation and recycling them is necessary. The manipulation with the wastes shall be in compliance with the national laws.

Classification of the wastes:

Polyvinylchloride wastes wastes of developers
Lead wastes wastes of fixing bath

The product has CE marking and has been produced and marketed in conformity with a quality system according to the international standard EN ISO 9001:2000, EN ISO 13485:2003.